

GHS-MSDS

MSDS_Number : No Data

1. Identification

- A. Product name : ROCKHARD CLEAR COAT T-2000
○ Usage category : Topcoat
- B. Recommended Use and Restriction on Use
○ General use :
○ Restriction on use : Restricted to use other than recommended use
- C. Manufacturer / Supplier / distributor information
○ Company name : Xtreme Polishing Systems
○ Address : 2200 NW 32 St, Pompano Beach, FL, USA
○ Emergency telephone number : US (CHEMTEL): 1(800) 255-3924

2. Hazard identification

- A. GHS Classification
Flammable liquids Category 2
Acute toxicity (inhalation: vapor) Category 4
Serious eye damage/irritation Category 1
Serious eye damage/irritation Category 2A
Specific target organ toxicity(Single exposure) Category 3 (respiratory irritation)
Skin sensitization Category 1
Skin corrosion/irritation Category 1
Skin corrosion/irritation Category 2
Acute toxicity (oral) Category 5
Acute toxicity (dermal) Category 5

B. GHS label elements

- Hazard symbols



- Signal words : DANGER
- Hazard statements :
H225 Highly flammable liquid and vapour
H332 Harmful if inhaled
H318 Causes serious eye damage
H319 Causes serious eye irritation
H335+H336 May cause respiratory irritation, May cause drowsiness and dizziness.
H317 May cause an allergic skin reaction
H314 Causes severe skin burns and eye damage
H315 Causes skin irritation
H303 May be harmful if swallowed.
H313 May be harmful in contact with skin.
- Precautionary statements
- Prevention
P210 Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. no smoking
P223 Do not contact with water
P240 Ground container and receiving equipment
P241 Use explosion-proof equipment (electricity, ventilation, lighting, etc.)
P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands and contact areas thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- Response
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P310 Immediately call a POISON CENTER or doctor/physician.
P337+P313 If eye irritation persists, get medical attention / attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment



P362+P364 Take off contaminated clothing and wash before reuse.
P301+P330+P331 Rinse mouth if swallowed. Do not induce vomiting.
P363 Wash contaminated clothing before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
- Storage
P403+P235 Store in a well-ventilated place. Keep cool.
P403+P233 Store in a well-ventilated place. Keep container tightly closed
P405 Save by locking.
- Disposal
P501 Dispose of the contents and containers in accordance with waste-related laws.

C. Other hazards which do not result in classification : (NFPA Classification)

Chemical Name	NFPA grade	Health	Flammability	Reactivity	GHS Classification
tert-Butyl acetate		2	3	0	H303, H313, H332, H335+H336
4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane		1	1	0	H317
3-Aminopropyltriethoxysilane		3	1	1	H303, H313, H314, H317, H318, H319
Tetraethoxy silane		2	3	1	H303, H313, H332, H335+H336

3. Composition/information on ingredients

Chemical Name	Trade names and Synonyms	CAS-NO	Content(%)
4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane	4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane	30583-72-3	7
tert-Butyl acetate	tert-Butyl acetate	540-88-5	80
Tetraethoxy silane	Tetraethoxy silane	78-10-4	6
3-Aminopropyltriethoxysilane	3-Aminopropyltriethoxysilane	919-30-2	7

4. First-aid measures

A. Eye Contact : Flush exposed eyes with plenty of water for more than 15minutes.
If irritation, pain, swelling, tears or glaring happens, take medical assistant immediately
Do not rub your eyes.
If you wear a contact lenses, remove them first.

B. Skin Contact : Remove exposed clothing, and wash off exposed area with soap and water.
If symptoms like irritation or pain occurs, take medical assistant immediately.
Wash off with soap and water for more than 15 minutes. And take medical assistant immediately.
If symptoms like redness or irritation occurs, take medical assistant immediately.
Wash carefully after handling.
Wear gloves while washing the patient and avoid contact with exposed clothes.

C. Inhalation : Avoid from exposure, and move into an area with fresh air.
If not breathing, perform the artificial respiration.
If inhaled or swallowed, do not perform the inhalation phase of breathing
Perform the artificial respiration, using the pocket mask with one way valves or other respiratory medical devices.
If hard to breathe, administering oxygen
Remove contaminated clothing and shoes, and isolate it.
Take a medical assistant immediately.

D. Ingestion Contact : Please be advised by doctor whether induction of vomit is demanded or not.
vomiting occurs, keep head below hips to prevent aspiration into lungs.
If ingested large quantity, take medical assistant.
Take proper medical assistant by symptoms.
It is need to be considered that early removal of some ingested material by gastric lavage must be weighed against potential complications of bleeding or perforation
Flush mouth with water immediately.

E. Notes to Physician : Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. Fire-fighting measures

A. Suitable (Unsuitable) extinguishing media
○ Suitable extinguishing media : Powder extinguishing agent, gaseous Extinguishing Agent, and regular foam.
○ (Unsuitable) extinguishing media : Avoid digestion using direct water.
Avoid use waterjet as fire extinguishing agent.
Avoid extinguishing fire with halogenting agent.
○ Case of big fire : Spread large amount of the extinguishing agent as a mist form with staying against wind.
Stay away more than 800m to avoid tank explosion.
Use appropriate protective device depend on the situation.

B. Specific hazards arising from the chemical
○ Pyrolystate : Carbon dioxide, toxic carbon compounds/Nitrogen compounds/sulfur compounds
Irritating and highly toxic gases may produced during the combustion by pyrolysis or combustion itself.
○ Fire and Explosion danger : Risk of medium-sized fire.
Aqueous (Exclude water-soluble one) products does not have risk of fire or explosion hazard by itself.





Vapor may be released to the ignition source and ignited.
May form explosive mixture at or above ignition point
Container may explode when heating
Leakages may fire / explosion hazard and could be easily ignited by heat, sparks or flames.
Vapors may explode indoors, outdoors, and in drains

- C. Special protective actions for fire-fighters
- Personal Precautions, protective equipment : Gas mask or air respirator, heat resistant clothing, heat resistant helmet, heat resistant gloves, heat resistant boots
 - Emergency procedures : Use appropriate extinguishing agents to catch fire.
If there is no risk, moving containers away from fire.
Cooling containers with water long time after extinguish fire.
Block the area except for the fire-suppression personnel.
Protect others from access and prohibit access to dangerous areas.
Tell the fire department, location of the fire and the hazardous features.
Use an unmanned fire extinguishing device, in case of large-sized fire. If not, leave it to burn.
Avoid inhalation of the substance or combustion products.
Do not approach if the tank is on fire.

6. Accidental release measures

- A. Personal Precautions, protective equipment and emergency procedures
- Personal Precautions, protective equipment : Appropriate protective equipment / protection / protective gloves
 - Emergency procedures : Take an action to block the leakage if there is no risk.
Spray water to reduce amount of steam.
The operator should wear appropriate protective equipment (see section "8. Exposure Protection and Personal Protection") to avoid contact with the eyes and skin and inhalation.
- B. Environmental precautions
- Atmosphere : Do install the local ventilations and full ventilation system
Using local ventilation to Minimize the exposure to worker.
 - Soil : Trap spilled material at bottom in deep water pockets, excavated holding areas or within sand bag barriers.
Use absorbent to collect the appropriate container.
 - Under water : Use absorbent to collect the appropriate container.
Collect spilled material with mechanic devices
- C. Methods and materials for containment and cleaning up
- Small spill : Absorb for use sand or other non-combustible material.
Move to appropriate container for disposal of spilled material collected.
 - Large spill : Prohibit access of unnecessary people, isolate hazard area to secure.
Notify to central and local government, when emissions are above regulation.

7. Handling and storage

- A. Precautions for safe handling : Keep or handle followed by Dangerous goods Safety Management Act
Ground for preventing the static discharge
Seal the container for minimizing the petroleum steam
Use local ventilations and a full ventilation system when handling
Wash carefully after handling.
Avoid contact with prohibited materials in mixture.
Do not handle until read and understood all safety precautions.
Do not inhale vapor for long-term or repeatedly.
Avoid contact with heat, sparks, flames or other sources of ignition.
Do not take contaminated clothings away from the work area.
Storing with combustible substances such as stained clothes or paper may cause fire by spontaneous ignition. Thus do not stack it, and keep it in a non-flammable container with cap filled with water and dispose it.
- B. Conditions for safe storage, including any incompatibilities : Because of evaporation and contamination concerns, airtight the container and store in a well-ventilated building.
Avoid direct sunlight while storing outdoor.
Storage temperature: 5 ~ 35 °C
Avoid strong oxidizing agents, acid.
Store at appropriate temperature according to the isolation location, freezing caution, high temperature body caution.
No open fire.
Store in a cool, dry, well-ventilated area.
Check periodically for leaks
Store in accordance with all current law and regulations.
Store in original container only.
Prevent static electricity and do not store near heat sources.
Collect in an airtight container to dispose.
Store away from waterworks and sewers.

8. Exposure controls/personal protection

- A. Exposure Limits
- tert-Butyl acetate
 - ACGIH : NO DATA
 - Biological exposure indices : NO DATA
 - 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - ACGIH : NO DATA
 - Biological exposure indices : NO DATA





- 3-Aminopropyltriethoxysilane
 - ACGIH : NO DATA
 - Biological exposure indices : NO DATA
- Tetraethoxy silane
 - ACGIH : NO DATA
 - Biological exposure indices : NO DATA

B. Engineering Controls :

- ▷ Do install the local ventilations and full ventilation system
- ▷ Using local ventilation to Minimize the exposure to worker.
- ▷ NO DATA
- ▷ NO DATA

C. Personal Protective Equipment

- Respiratory protection : Respirators should be authorized by Occupational Safety and Health Agency Unknown concentration or other life threatening danger is imminent: Supplied air respirator(Hybrid airline respirator), and Self contained breathing apparatus(full face)
Consider warning properties before use.
Respiratory protection may be needed, while frequent use or heavy exposure.
Respiratory protection is ranked in order from minimum to maximum
If there is possibility of direct contact or exposure to these substances should wear a authorized dust-proof mask or respirator for organic compounds
- Eye protection : Install washing facilities and an emergency washing facilities close to workplace.
Let workers do wear the safety glasses in case hazard caused by mist may be expected.
If there is possibility of direct contact or exposure to these substances should wear authorized safety glasses or mask.
- Hand protection : If there is possibility of direct contact or exposure to these substances should wear authorized safety gloves for chemicals.
- Skin protection : If there is a possibility of direct contact or exposure to the substance Wear protective clothing for chemical substances

9. Physical and chemical properties

- A. Appearance :
- B. Odor :
- C. Odor threshold : NO DATA
- D. PH : NO DATA
- E. Melting point/Freezing point(°C) : NO DATA
- F. Initial Boiling Point/Boiling Ranges(°C) : NO DATA
- G. Flash point(°C) : 15.5
- H. Evaporating Rate : NO DATA
- I. Flammability(solid, gas) : NON Flammable
- J. Upper/Lower Flammability or explosive limits : NO DATA
- K. Vapour pressure : NO DATA
- L. Solubility : NO DATA
- M. Vapour density : NO DATA
- N. Specific gravity : 0.89
- O. Partition coefficient of n-octanol/water : NO DATA
- P. Autoignition temperature(°C) : NO DATA
- Q. Decomposition temperature(°C) : NO DATA
- R. Viscosity : ~100 cps

S. Molecular weight : NO DATA

10. Stability and reactivity

- A. Chemical stability : NO DATA
- B. Possibility of hazardous reactions : Do not contact with heat, spark, flame or other flammable sources
Avoid contaminants and friction
- C. Conditions to avoid : Oxidation agent, metal and combustible materials
- D. Hazardous decomposition products : Thermal decomposition products (carbon etc..)

11. Toxicological information

- A. Information on the likely routes of exposure
- Respiratory tracts : Adverse lung effects, Dyspnoea, Hypothermia, Vomitting
 - Oral : Vomitting, Diarrhea, Stomach pain, Irregular heartbeat
 - Skin : Irritation, Burn, Adverse nerve effects
 - Eye : Irritation, eye damage





B. Delayed and immediate effects and also chronic effects from short and long term exposure

- tert-Butyl acetate
 - Acute toxicity
 - Oral : LD50 4100 mg/kg Rat
 - Dermal : LD50 > 2000 mg/kg Rabbit
 - Inhalation : LD50 > 2000 mg/kg Rabbit
 - Skin corrosion/irritation : 500 μ l / 24 H skin - rabbit weakstimulus
 - Serious eye damage/irritation : 100 mg eyes-rabbit mild irritant
 - Respiratory sensitization : NO DATA
 - Skin sensitization : NO DATA
 - Carcinogenicity
 - IARC : NO DATA
 - OSHA : NO DATA
 - ACGIH : NO DATA
 - NTP : NO DATA
 - EU CLP : NO DATA
 - Germ cell mutagenicity : NO DATA
 - Reproductive toxicity : NO DATA
 - STOT-single exposure : NO DATA
 - STOT-repeated exposure : NO DATA
 - Aspiration hazard : NO DATA
- 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - Acute toxicity
 - Oral : NO DATA
 - Dermal : NO DATA
 - Inhalation : NO DATA
 - Skin corrosion/irritation : NO DATA
 - Serious eye damage/irritation : NO DATA
 - Respiratory sensitization : NO DATA
 - Skin sensitization : NO DATA
 - Carcinogenicity
 - IARC : NO DATA
 - OSHA : NO DATA
 - ACGIH : NO DATA
 - NTP : NO DATA
 - EU CLP : NO DATA
 - Germ cell mutagenicity : NO DATA
 - Reproductive toxicity : NO DATA
 - STOT-single exposure : NO DATA
 - STOT-repeated exposure : NO DATA
 - Aspiration hazard : NO DATA
- 3-Aminopropyltriethoxysilane
 - Acute toxicity
 - Oral : LD50 = 1570 mg/kg Rat
 - Dermal : LD50 = 4290 mg/kg rabbit
 - Inhalation : LD50 = 4290 mg/kg rabbit
 - Skin corrosion/irritation : when the dilution of rabbit test actually showed severe Irritation to accept, but when undiluted necrosis and ulcer
 - Serious eye damage/irritation : Severe irritant to rabbit 13 days observation period and necrosis appears
 - Respiratory sensitization : NO DATA
 - Skin sensitization : 7 of 30 guinea pigs indicates that sensitization
 - Carcinogenicity
 - IARC : NO DATA
 - OSHA : NO DATA
 - ACGIH : NO DATA
 - NTP : NO DATA
 - EU CLP : NO DATA
 - Germ cell mutagenicity : In vitro Mammalian cell gene mutation, Chromated exchange assay at the time when Negative Negative in vivo Mouse micronucleus assay
 - Reproductive toxicity : In vitro Mammalian cell gene mutation, Chromated exchange assay at the time when Negative Negative in vivo Mouse micronucleus assay
 - STOT-single exposure : NO DATA
 - STOT-repeated exposure : NO DATA
 - Aspiration hazard : NO DATA
- Tetraethoxy silane
 - Acute toxicity
 - Oral : LD50 = 6270 mg/kg Rat
 - Dermal : LD50 = 5859 mg/kg rabbit
 - Inhalation : LD50 = 5859 mg/kg rabbit
 - Skin corrosion/irritation : Reported on skin stimulus.
 - Serious eye damage/irritation : Tests applied to the eyes of rabbits recognized that change is reported within 24 hours of recovery based on the real prize is judged Has No irritant. Applied to the eye of the rabbit eye irritation test in hardness has been reported is recognized.
 - Respiratory sensitization : NO DATA
 - Skin sensitization : NO DATA
 - Carcinogenicity
 - IARC : NO DATA
 - OSHA : NO DATA
 - ACGIH : NO DATA
 - NTP : NO DATA
 - EU CLP : NO DATA
 - Germ cell mutagenicity : NO DATA





- Reproductive toxicity : NO DATA
- STOT-single exposure : Severe anemia in guinea pigs, Narcotic effects have been reported. Reported airway irritation in humans.
- STOT-repeated exposure : NO DATA
- Aspiration hazard : NO DATA

12. Ecological information

A. Ecotoxicity

- ☐ tert-Butyl acetate
 - Fish : LC50 327 mg/l 96 hr
 - Crustaceans : EC50 5000 mg/l 24 hr
 - Algae : NO DATA
- ☐ 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - Fish : NO DATA
 - Crustaceans : NO DATA
 - Algae : NO DATA
- ☐ 3-Aminopropyltriethoxysilane
 - Fish : LC50 $\geq$ 934 mg/l 96 hr Brachydanio rerio
 - Crustaceans : EC50 = 331 mg/l 48 hr Daphnia magna
 - Algae : EC50 = 603 mg/l 72 hr (Scenedesmus subspicatus)
- ☐ Tetraethoxy silane
 - Fish : NO DATA
 - Crustaceans : NO DATA
 - Algae : NO DATA

B. Persistence and degradability

- ☐ tert-Butyl acetate
 - Persistence : log Kow 1.76
 - Degradability : NO DATA
- ☐ 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - Persistence : NO DATA
 - Degradability : NO DATA
- ☐ 3-Aminopropyltriethoxysilane
 - Persistence : log Kow = 0.31 (Estimates)
 - Degradability : NO DATA
- ☐ Tetraethoxy silane
 - Persistence : NO DATA
 - Degradability : NO DATA

C. Bioaccumulative potential

- ☐ tert-Butyl acetate
 - Bioaccumulative potential : NO DATA
 - Biodegradation : NO DATA
- ☐ 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - Bioaccumulative potential : NO DATA
 - Biodegradation : NO DATA
- ☐ 3-Aminopropyltriethoxysilane
 - Bioaccumulative potential : NO DATA
 - Biodegradation : Biodegradability = 67 (%) 28 day
- ☐ Tetraethoxy silane
 - Bioaccumulative potential : NO DATA
 - Biodegradation : NO DATA

D. Mobility in soil

- ☐ tert-Butyl acetate
 - ▷ NO DATA
- ☐ 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - ▷ NO DATA
- ☐ 3-Aminopropyltriethoxysilane
 - ▷ NO DATA
- ☐ Tetraethoxy silane
 - ▷ NO DATA

E. Other adverse effects

- ☐ tert-Butyl acetate
 - ▷ NO DATA
- ☐ 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - ▷ NO DATA
- ☐ 3-Aminopropyltriethoxysilane
 - ▷ Shellfish NOEC = 94mg/L/48hr (Cyclops)
- ☐ Tetraethoxy silane
 - ▷ NO DATA

13. Disposal considerations

A. Disposal methods : Disposal material should keep in the airtight container, and consign according to Waste Material Management Act

Pre-treat with oil-water separation method when it is available.

Recycle the recyclable materials, such as organic solvents, and then incinerate the residue at high temperature.

To prevent environmental pollution, dispose it to a licensed waste disposal company.

B. Special precautions for disposal : Business that discharge business waste shall process them selves, or delegate





to waste treatment processor, recycler, or waste treatment operator.
Dispose of waste in accordance with all applicable laws and regulations.

14. Transport information

- A. UN number(IMDG CODE/IATA DGR) : 1263
- B. Proper shipping name : Paint (including paint, lacquer, enamel, colorants, shellac solutions, varnish, polish, liquid filler and liquid lacquer sealer) or related materials (including paint diluent and reductant).
- C. Hazard class : 3
- D. Packing group(IMDG CODE/IATA DGR) : II
- E. Marine pollutant : N/A
- F. Special precautions for user related to transport or transportation measures
Local transport follows in accordance with Dangerous goods Safety Management
Package and transport follow in accordance with Department of Transportation
 - EmS FIRE SCHEDULE : F-E
 - EmS SPILLAGE SCHEDULE : S-E

15. Regulatory information

- tert-Butyl acetate
 - Information of EU Classification
 - ▷ Classification : NO DATA
 - ▷ Risk Phrases : NO DATA
 - ▷ Safety Phrase : NO DATA
 - U.S. Federal regulations
 - ▷ OSHA PROCESS SAFETY (29CFR1910.119) : NO DATA
 - ▷ CERCLA Section 103 (40CFR302.4) : 2267.995 kg 5000 lb
 - ▷ EPCRA Section 302 (40CFR355.30) : NO DATA
 - ▷ EPCRA Section 304 (40CFR355.40) : NO DATA
 - ▷ EPCRA Section 313 (40CFR372.65) : NO DATA
 - Rotterdam Convention listed ingredients : NO DATA
 - Stockholm Convention listed ingredients : NO DATA
 - Montreal Protocol listed ingredients : NO DATA
- 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane
 - Information of EU Classification
 - ▷ Classification : NO DATA
 - ▷ Risk Phrases : NO DATA
 - ▷ Safety Phrase : NO DATA
 - U.S. Federal regulations
 - ▷ OSHA PROCESS SAFETY (29CFR1910.119) : notapplicable
 - ▷ CERCLA Section 103 (40CFR302.4) : notapplicable
 - ▷ EPCRA Section 302 (40CFR355.30) : notapplicable
 - ▷ EPCRA Section 304 (40CFR355.40) : notapplicable
 - ▷ EPCRA Section 313 (40CFR372.65) : notapplicable
 - Rotterdam Convention listed ingredients : NO DATA
 - Stockholm Convention listed ingredients : NO DATA
 - Montreal Protocol listed ingredients : NO DATA
- 3-Aminopropyltriethoxysilane
 - Information of EU Classification
 - ▷ Classification : NO DATA
 - ▷ Risk Phrases : NO DATA
 - ▷ Safety Phrase : NO DATA
 - U.S. Federal regulations
 - ▷ OSHA PROCESS SAFETY (29CFR1910.119) : notapplicable
 - ▷ CERCLA Section 103 (40CFR302.4) : notapplicable
 - ▷ EPCRA Section 302 (40CFR355.30) : notapplicable
 - ▷ EPCRA Section 304 (40CFR355.40) : notapplicable
 - ▷ EPCRA Section 313 (40CFR372.65) : notapplicable
 - Rotterdam Convention listed ingredients : NO DATA
 - Stockholm Convention listed ingredients : NO DATA
 - Montreal Protocol listed ingredients : NO DATA
- Tetraethoxy silane
 - Information of EU Classification
 - ▷ Classification : NO DATA
 - ▷ Risk Phrases : NO DATA
 - ▷ Safety Phrase : NO DATA
 - U.S. Federal regulations
 - ▷ OSHA PROCESS SAFETY (29CFR1910.119) : notapplicable
 - ▷ CERCLA Section 103 (40CFR302.4) : notapplicable
 - ▷ EPCRA Section 302 (40CFR355.30) : notapplicable
 - ▷ EPCRA Section 304 (40CFR355.40) : notapplicable
 - ▷ EPCRA Section 313 (40CFR372.65) : notapplicable
 - Rotterdam Convention listed ingredients : NO DATA
 - Stockholm Convention listed ingredients : NO DATA
 - Montreal Protocol listed ingredients : NO DATA

16. Other information





A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS,NLM, SIDS, IPCS

B. Issue date : 2024-10-16

C. Revision number and Last date revised :

D. Other : " WWW.XTREMEPOLISHINGSYSTEMS.COM"

